
Anglia Plus Interlocking tiles





A single-lap interlocking concrete tile with the classic clay pantile profile.

Technical data

| Size of tile | 387mm x 230mm |
|--------------------|--------------------------------|
| Minimum pitch* | 30° Smooth (75mm headlap) |
| | 30° Granular (75mm headlap) |
| | 25° Smooth (100mm headlap) |
| Maximum pitch | 90° |
| Minimum headlap | 75mm |
| Maximum gauge | 312mm |
| Profile depth | d > 20mm |
| Cover width | 204mm (nominal) |
| Hanging length | 361mm (nominal) |
| Covering capacity | 15.7 tiles/m² at 75mm headlap |
| (net) | 17.1 tiles/m² at 100mm headlap |
| Weight of tiling | 47 kg/m² (0.46 kN/m²) |
| (approx.) | at 75mm headlap |
| | 51 kg/m² (0.50 kN/m²) |
| | at 100mm headlap |
| Battens required | 3.2 lin.m/m² at 75mm headlap |
| (net) | 3.5 lin.m/m² at 100mm headlap |
| Batten size | 38 x 25mm for rafters/supports |
| recommended | not exceeding 450mm centres |
| (fixed to BS 5534) | 50 x 25mm for rafters/supports |
| | not exceeding 600mm centres |
| Tile nails | 38mm x 3.35mm |
| Fixing clips | Eaves, verge and tile clips |

* The minimum recommended pitch and lap may be influenced by special circumstances, please refer to the Technical Advisory Service.



BS EN 490